

# Mini Leak Detection Sensor Featuring LoRaWAN® WS303



# Milesight WS303

is a tiny and mighty leakage detection sensor for detecting presence of water leaks and transmitting an alarm using LoRaWAN® technology. With this low power consumption technology, WS303 can work up to 5 years with a 590mAh battery. Compliant with Milesight D2D protocol, it can directly link with other Milesight devices to realize danger prevention and effectively prevent unnecessary loss. The wire-free WS303 can be easily used in smart offices, buildings, and houses. Users can receive real-time alarms via a built-in buzzer locally and a mobile App remotely. Combining with Milesight LoRaWAN® gateway and Milesight IoT Cloud, users can manage all sensor data remotely and visually.

### **FEATURES**

- Detect the presence of conductive liquids using a small water probe
- A replaceable built-in 590mAh battery with up to 5 years of life for wire-free power supply
- IP67 waterproof enclosure for harsh environment applications
- Embedded with a buzzer for real-time alarming

- Support Milesight D2D protocol to enable ultra-low latency and direct control without gateways
- Equipped with NFC for easy configuration
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with Milesight IoT Cloud solution

### **SPECIFICATIONS**

### Wireless Transmission

Technology LoRaWAN®, Milesight D2D

Frequency CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923-1&2&3&4

Tx Power 16dBm(868 MHz)/20dBm(915 MHz)/19dBm(470 MHz)

Sensitivity -137dBm @300bps

Mode OTAA/ABP Class A

## Leakage Detection

Liquid Type Conductive Liquid

Trigger Condition Once Liquid Level Reaches 0.5mm

### **Others**

Buzzer Support

Configuration NFC Configuration via Mobile App

Advanced Feature Milesight D2D Controller

# Physical Characteristics

Power Supply 1 × 590mAh CR2450 Lithium Battery

Battery Life\* 5 years (One hour leakage per week, 25°C)

Operating Temperature -10°C to +60°C

Relative Humidity 0% to 100% (Non-condensing)

Ingress Protection IP67

Dimension 63 × 63 × 14 mm

Material & Color ABS+PC, White

Installation 3M Tape Mounting, Desktop

<sup>\*</sup> Tested under laboratory conditions and for guideline purposes only.